2. Product Specifications and Comparison Chart

2-1 PAL Models (VP-L700U/L700/L710/L750/L750D/L770)

Operation	Description
Recording system	Video: 2 rotary heads Helical scanning FM Audio: FM monaural system
Video signal	PAL colour, CCIR standard
Usable cassette	VP-L700U : 8 mm, VP-L700/L710/L750/L750D/L770 : Hi8 or 8 mm
Tape speed	SP: 20.051 mm/sec
Speed mode	Record: SP only Playback: SP only.
Recording time	P5-120: 120 min.
FF or REW time	P5-120: approx. 8 min.
Image device	CCD (Charge Coupled Device)
Optical zoom ratio	22x
Focal length: f	3.6~79.2 mm
F	1.6
Filter diameter	46 mm
Focus system	Inner
Macro	Auto wide macro
Min. Illumination	0.3 lux (visible)
LCD monitor	
Size/Pic. cell	2.5 inch/123k
Method	TFT
Connectors	
Video out	Mini jack, 1 Vp-p, 75 ohms, Unbalanced
Audio out	Mini jack, 7.7 dBs, imp.: less than 820 ohms
External mic	Monaural ø3.5
General	
Power requirements	DC 8.4 V (1.5 A)
Power consumption ***Recording, LCD ON**	VP-L700U/L700/L710 : 5.4W, VP-L750/L750D/L770 : 5.9W
Built-in mic	Condenser mic, omni-directional
Built-in speaker	Dynamic, 0.5 W standard
Operating temperature	0°C to 40°C (32°F to 104°F)
Dimension (W * H * D)	101 * 104 * 174 mm
Weight	750 g

⌘ The technical specifications and design may be changed without notice.

W4-2.Product Specification-PAL 2/17/02 7:45 PM Page 2

2-2 Comparison Chart

2-2-1. PAL Models

Model / Features	PAL					
	VP-L700	VP-L700U	VP-L710	VP-L750	VP-L750D	VP-L770
Format	Hi8	8mm	Hi8	Hi8	Hi8	Hi8
Video Light	X	X	X	O	O	O
Remote Control	X	X	O	O	O	O
Audio	Mono	Mono	Mono	Mono	Mono	Mono
DIS	X	X	X	O	O	O
SNAP/SHOT	X	X	X	O	O	O
EVF	O	O	O	O	O	O
CVF	X	X	X	X	X	X
CCD	320K	320K	320K	320K	320K	320K
Digital Zoom Ratio	880X	880X	880X	880X	990X	880X